

DS-K1T502 Series Access Control Terminal

Release Notes (2022-07-22)

Device Model: DS-K1T502DBFWX, DS-K1T502DBFWX-C, DS-K1T502DBWX, DS-K1T502DBWX-C Naming Rule: D for Desfire&Mifare card B for Bluetooth F for Fingerprint W for Wi-Fi C for Camera	Firmware Version	AIS_FRACS_502_F1pro_EN_STD_V1.7.1_build220719 AIS_FRACS_502_F1pro_EN_NEU_V1.7.1_build220719
	Software	HikCentral AC: https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v1-3-0/ iVMS: https://www.hikvision.com/en/support/download/software/ivms4200-series/ Please add device to iVMS/HCP with port 80, the default port 8000 will not work

Reason of Upgrade

New model DS-K1T502 series access control terminals first time released.



New Features

1. High Protective level: IP65 & IK09 protections, as well as increased stability with zinc alloy materials
2. All-in-one: Manage access control, video intercoms, and video security with one device
3. Multiple authentication methods, including fingerprint, card, PIN code etc.
4. Remote control via the Hik-Connect mobile app
5. Support web configuration
6. **Capacity**

	Finger print	Card	Event	Bluetooth	Wi-Fi	Camera
DS-K1T502DBFWX	10,000	100,000 (Desfire card, Mifare 1 card)	300,000	Support	Support	N/A
DS-K1T502DBFWX-C						Support
DS-K1T502DBWX	N/A					N/A
DS-K1T502DBWX-C						Support

7. **ISAPI** protocol makes it easier to integrate with third-party software;
8. Remote video intercom and unlock door from **Hik-Connect** App on your mobile/Pad
9. Support **ISUP 5.0**(EHome 5.0) protocol to manage devices located in different location;

10. Network

Support TCP/IP and Wi-Fi, Bluetooth, adapt to LAN (network) or WAN (ISUP 5.0) network environment

Note: Bluetooth function is used to connect mobile APP to unlock the door; the APP will be released in 2022Q4


11. Function


- a. Video intercom with indoor/main station, hik-connect mobile app and iVMS4200/HikCentral; For apartment situation (both DS-K1T502 and indoor station are available), we recommend to add indoor station to hik-Connect only (do not add DS-K1T502 to Hik-Connect).

Note: If you add DS-K1T502 to Hik-Connect, it will call indoor station and Hik-Connect at the same time and you can answer from anyone of them.

For situation that indoor station is not available in the system, you can add DS-K1T502 directly to Hik-Connect

- b. Event linkage short video stored inside TF card (max 256GB supported), and search and play the video in event history.





Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

Note:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain errors known as errata, which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.
No. 555 Qianmo Road, Binjiang District, Hangzhou 310051,
China
Tel: +86-571-8807-5998
FAX: +86-571-8993-5635
Email: overseabusiness@hikvision.com