

DS-K1T642 Series MinMoe Terminal Release Notes (2020-12-08)

Device Model: DS-K1T642M DS-K1T642E DS-K1T642MF DS-K1T642EF DS-K1T642MW DS-K1T642EW DS-K1T642MFW DS-K1T642EFW Naming Rule: M for M1 card, E for EM card, F for fingerprint, W for Wi-Fi	Firmware Version	ACS_641_AI3_EN_GM_V3.1.7_build201127
	SDK	Latest version
	iVMS-4200 Client Version	Latest baseline

Reason of Upgrade

Add new features, fix bugs, enhance products quality and meet customers' requirements.

New Feature

1. Support dual backup to avoid upgrade and bricking
2. Add turning on the infrared light step when booting, and improve the user experience

Modified Features

1. Fix the message format problem of ISAPI access control event capability set
2. Optimize the translation of mask-related menus in Russian language
3. Improve face recognition algorithm to reduce misidentification of non-face objects
4. Optimize the web page preview effect in WIFI environment

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

Note:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain errors known as errata, which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.
No. 555 Qianmo Road, Binjiang District, Hangzhou 310051,
China
Tel: +86-571-8807-5998
FAX: +86-571-8993-5635
Email: overseabusiness@hikvision.com